



Afri Cote CHLORINATED RUBBER PAINT

PRODUCT

Afri Cote Chlorinated Rubber Paint is a hard wearing coating with good gloss and colour retention, flame retardant & anto corrosive properties. It is Chlorinated Rubber- Alkyd modified system specially developed for mild to sever corrosive environment.

FINISH

Gloss

COLOURS

Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.

AREA OF APPLICATION

Afri Cote Chlorinated rubber Paint is Suitable for use in a variety of mild to aggressive corrosive environments including industrial & coastal areas, on the substrates such as structural steel, towers, bridges, industrial equipments etc.It has Excellant sea water resistance, good chemical resistance and good flame retardant properties.It can withstand continuous dry heat at up to 80 Deg. C.

<u>TECHNICAL SPECIFICATION</u>	
SPECIFIC GRAVITY	1.1 ± 0.1
COVERAGE	Approximately 8 to 10 square meters per litre per coat depending on the surface.
DRYING TIME	Surface Dry: 1 - 1.5 Hours Hard dry: 2 - 4 Hours Recoating: After 24 Hours
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Afri Cote Chlorinated Rubber paint can be applied directly by use of brush, dipping or spraying.
EQUIPMENT	Can be applied using brush, dipping or by spraying. Thin and stir as per requirement
THINNING	It can be thinned with Afri cote Chlorinated Rubber Paint thinner depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with Afri Cote CR Paint thinner.
PACKING SIZE	20 Litres, 4 Litres, 1 Litre