



MAROO HIGH GLOSS ENAMEL

PRODUCT Maroo High Gloss Enamel is an economy quality synthetic enamel based on synthetic alkyd resin and pigmented with selected pigments. It is resistant to routine washing and scrubbing.

FINISH Glossy

COLOURS Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.

AREA OF APPLICATION Maroo High Gloss Enamel is recommended for the decoration and protection of interior and exterior surfaces like metals, wood, walls, plaster, brick work, stone work etc. where a glossy and durable finish is required.

<u>TECHNICAL SPECIFICATION</u>	
SPECIFIC GRAVITY	1.00 ± 0.05
COVERAGE	Approximately 13 to 14 m ² /litre per coat on smooth surface
DRYING TIME	Surface Dry : 3 - 5 Hours
	Hard dry : 6 - 8 Hours
	Recoating : After 24 Hours
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Smoothen out with sand paper to provide required smoothness. Maroo High Gloss Enamel should be applied over appropriately primed & undercoated surfaces
EQUIPMENT	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
THINNING	It can be thinned with white spirit depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with white spirit.
PACKING SIZE	20 Litres, 4 Litres, 1 Litre, ½ Litre, ¼ Litre