

TRADE



Colourtrend MASTER GLOSS ENAMEL

PRODUCT	Colourtrend Master Gloss Enamel is a trade quality synthetic enamel with a hard and brilliant finish based on a quality alkyd resin and selected quality pigments of proven performance. It is resistant to normal abrasion, moderate condensation and moderate climatic conditions.
FINISH	Glossy
COLOURS	Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.
AREA OF APPLICATION	Colourtrend Master Gloss Enamel is recommended for Interior and Exterior surfaces like metals, wood, walls, plaster, brick work, stone work etc. under domestic & industrial applications. It is also used for exterior trims where a gloss finish, water resistance and accent on colour is required.

TECHNICAL SPECIFICATION

SPECIFIC GRAVITY	1.03 ± 0.05
COVERAGE	Approximately 14 to 15 m ² /litre per coat on smooth surface
DRYING TIME	Surface Dry : 3 - 5 Hours
	Hard dry : 6 - 8 Hours
	Recoating : After 24 Hours
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

METHOD OF APPLICATION

SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Smoothen out with sand paper to provide required smoothness. Colourtrend Master Gloss Enamel should be applied over appropriately primed & undercoated surfaces.
EQUIPMENT	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
THINNING	It can be thinned with white spirit depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with white spirit.
PACKING SIZE	20 Litres, 4 Litres, 1 Litre