



Afri Cote STONE FINISH

PRODUCT Afri Cote Stone Finish is a 100% pure acrylic emulsion based eco-friendly textured coating reinforced with Naturally available specially selected stone chips. It has excellent Ultra violet and alkali resistance. Afri Cote Stone Finish provides long life protection with a good crack bridge ability property. It contains anti fungal and anti bacterial additives.

FINISH Textured finish/ Matt

TEXTURE 1.0 mm, 2.0 mm, 3.0 mm.

COLOURS Naturally available stone colours. Please refer to our Afri Cote Stone finish catalogue for available range of colours.

AREA OF APPLICATION Afri Cote Stone Finish is recommended for both interior and exterior surfaces like concrete, stone, plaster, gypsum board, asbestos, brick works etc. It can also be applied on properly primed/ sealed wooden surfaces like chipboard, block board, plywood etc. Different types of textured designs can be obtained depending on size of aggregates used and application techniques done by professional applicators. It can be over coated with Africoat Clear Glaze to reduce the dirt pick up and increase durability. Major areas of application are apartments, buildings, offices, public areas etc.

<u>TECHNICAL SPECIFICATION</u>	
SPECIFIC GRAVITY	1.50 - 2.00 Depending on type of texture
COVERAGE	Approximately 1 m ² per 3.5 - 4.0 Kilos
DRYING TIME	Surface dry - 1 Hour, Hard dry - 24 Hours.
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Africoat Stone Finish should be applied over appropriately primed & undercoated surfaces
EQUIPMENT	Can be applied using a metal trowel. Thin and stir as per requirement
THINNING	It can be thinned with fresh water for ease of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with water.
PACKING SIZE	25 Kgs, 6 Kgs