



Afri Cote Plaster Filler

PRODUCT Afri Cote Plaster Filler is a ready to use filler for masonry and wooden surface. It has an excellent adhesion, minimum shrinkage, fast drying and good sandability. It can be used on masonry surfaces, plasters, plaster boards and wall boards.

FINISH Matt

COLOURS White, Soft white

AREA OF APPLICATION Afri Cote Plaster Filler is recommended for use as a skim coat for masonry surfaces plasters, plaster boards and wall boards. It fills the unevenness of the surface and gives a good levelling—resulting in better finishing of the subsequent coats.

<u>TECHNICAL SPECIFICATION</u>	
SPECIFIC GRAVITY	1.60 ± 0.05
COVERAGE	Approximately 3 to 5 square meters per kg depending on surface
DRYING TIME	15 - 30 Mins Sand ability & Overcoating after 1 Hour
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
SURFACE PREPARATION	Ensure that the surface is clean, dry and free from oil, grease or loose material. Apply Afri cote plaster filler and level it with the masonry trowel in order to fill the holes and unevenness of the surface. After drying, make a light sanding with sand paper in order to get a smooth even surface.
EQUIPMENT	Can be applied using trowel. Thin and stir as per requirement
THINNING	It can be thinned with fresh water depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with fresh water.
PACKING SIZE	25 Kgs, 6 Kgs.