



MAROO PLASTIC DISTEMPER

PRODUCT Maroo Plastic Distemper is an acrylic co-polymer based economical distemper paint with a smooth, flat finish. It contains anit fungal and anti bacterial additives.

FINISH Matt

COLOURS Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.

AREA OF APPLICATION Maroo Plastic Distemper is recommended for masonry application and decoration of interior surfaces like concrete, plaster, gypsum board, asbestos, walls, ceilings etc. where a matt finish is required.

TECHNICAL SPECIFICATION	
SPECIFIC GRAVITY	1.50 ± 0.05
COVERAGE	Approximately 9 to 11 m ² /litre per coat depending on porocity of surface
DRYING TIME	Recoating after 1 - 2 Hours
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

METHOD OF APPLICATION	
SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Smoothen out with sand paper to provide required smoothness. Maroo Plastic Distemper Emulsion should be applied over appropriately primed & undercoated surfaces
EQUIPMENT	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
THINNING	It can be thinned with fresh water depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with water.
PACKING SIZE	20 Litres, 4 Litres