

PREMIUM



***Afri Cote* QUICK AIR DRYING ENAMEL (QAD)**

PRODUCT

Afri Cote Quick Air Drying Enamel is a very quick dry synthetic enamel based on specially selected resins & pigments. It has an excellent gloss finish, flexibility, hardness & full bodied appearance.

FINISH

Gloss

COLOURS

Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.

AREA OF APPLICATION

Afri Cote Quick Air Dry Enamel is recommended for the protection of metal surfaces where an economical, durable and fast dry coating is required. Major areas of application include Automotive vehicles e.g. trucks, agricultural machineries & exterior metal sign boards etc.

TECHNICAL SPECIFICATION

| | |
|-------------------------|---|
| SPECIFIC GRAVITY | 1.00 ± 0.01 |
| COVERAGE | Approximately 8 to 10 square meters per litre coat on smooth surface |
| DRYING TIME | Surface Dry: 5 - 10 Hours Hard dry: 8 - 10 Hours Recoating: After 24 Hours |
| REMARK | Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time. |

METHOD OF APPLICATION

| | |
|----------------------------|--|
| SURFACE PREPARATION | Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Africote Quick Air Dry Enamel can be applied directly by use of brush, dipping or spraying. |
| EQUIPMENT | Can be applied using brush, dipping or by spraying. Thin and stir as per requirement |
| THINNING | It can be thinned with Maroo high gloss thinner depending on type of application. |
| EQUIPMENT CLEANING | Equipment should be cleaned immediately after use with high gloss thinner. |
| PACKING SIZE | 20 Litres, 4 Litres, 1 Litre |