

PREMIUM



Afri Cote Sanding Sealer

PRODUCT

Afri Cote NC Sanding Sealer is a specially formulated fast drying sanding sealer based on short oil alkyd & nitrocellulose. It has an excellent sanding ability, quick drying & filling properties.

FINISH

Semi - Matt

COLOURS

Clear

AREA OF APPLICATION

Afri Cote NC Sanding Sealer is recommended for use as a base coat for different types of wooden surfaces like veneer, plywood, hardwood etc. It fills the pores & seals the surface without hiding the wooden grains. NC Sanding Sealer is a fast drying coating, thus can be sanded down in 30 Mins to allow for application of subsequent coats.

TECHNICAL SPECIFICATION

SPECIFIC GRAVITY	0.99 ± 0.05
COVERAGE	Approximately 7 to 10 square meters per litre coat depending on surface
DRYING TIME	10 - 15 Mins Sand ability & Overcoating after 30 Mins
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

METHOD OF APPLICATION

SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. For better performance of this product, apply 2 coats and sand down after each coat.
EQUIPMENT	Can be applied using brush or spraying. Thin and stir as per requirement
THINNING	It can be thinned with Maroo high gloss thinner depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with high gloss thinner.
PACKING SIZE	20 Litres, 4 Litres, 1 Litre