



Afri Cote SPRAY PLASTER

PRODUCT Afri Cote Spray plaster is an acrylic emulsion based eco-friendly coating reinforced with Specific graded fillers. It gives different type of designs & textures depending on the application method. Afri Cote Spray plaster is suitable for Ceiling decoration & provides long life protection with a good crack bridge ability property. It contains anti fungal and anti bacterial additives.

FINISH Matt Finish

TEXTURE Smooth / Textured finish Depending on application method

COLOURS White / Soft White

AREA OF APPLICATION Afri Cote Spray plaster is recommended for interior surfaces like concrete, stone, plaster, gypsum board, asbestos, brick works etc. It can be applied on properly primed/sealed wooden surfaces like chipboard, block board, plywood etc. Different types of designs can be obtained depending on application techniques done by professional applicators. It can be over coated with Africote range of colours & glaze for different effects & durability. Major areas of application are apartments, buildings, offices, public areas etc.

<u>TECHNICAL SPECIFICATION</u>	
SPECIFIC GRAVITY	1.50 -1.60
COVERAGE	Approximately 1 m ² per 0.5 - 2.5 Kilos depending on type of design required.
DRYING TIME	Surface dry - 1 Hour, Hard dry - 24 Hours.
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Africoat Spray plaster should be applied over appropriately primed & undercoated surfaces
EQUIPMENT	Can be applied using a trowel, roller or spray application. Thin and stir as per requirement
THINNING	It can be thinned with fresh water for ease of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with water.
PACKING SIZE	25 Kgs, 6 Kgs