

PREMIUM



# Colourtrend EGGSHELL ENAMEL

- PRODUCT** Colourtrend Eggshell Enamel is a high quality synthetic enamel with an exceptionally tough and smooth finish based on a synthetic alkyd resin and a carefully selected range of high quality pigments. Colourtrend Eggshell Emulsion has a semi-gloss finish exhibiting a percentage shine of normal gloss products.
- FINISH** Semi-gloss
- COLOURS** Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.
- AREA OF APPLICATION** Colourtrend Eggshell Enamel is recommended for both Interior and Exterior surfaces like metals, wooden surfaces, concrete, plaster etc. It is also used for doors, garden furniture & fittings and generally for exterior trims where a sheen finish, water and wear resistance are required. major areas of application are apartments, offices, kitchens, bathrooms etc.

## TECHNICAL SPECIFICATION

<b>SPECIFIC GRAVITY</b>	1.20 ± 0.05
<b>COVERAGE</b>	Approximately 13 to 15 m <sup>2</sup> /litre per coat on smooth surface
<b>DRYING TIME</b>	Surface Dry : 2 - 4 Hours
	Hard dry : 5 - 7 Hours
	Recoating : After 16 Hours
<b>REMARK</b>	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

## METHOD OF APPLICATION

<b>SURFACE PREPARATION</b>	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Smoothen out with sand paper to provide required smoothness. Colourtrend Eggshell Enamel should be applied over appropriately primed & undercoated surfaces
<b>EQUIPMENT</b>	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
<b>THINNING</b>	It can be thinned with white spirit depending on type of application.
<b>EQUIPMENT CLEANING</b>	Equipment should be cleaned immediately after use with white spirit.
<b>PACKING SIZE</b>	20 Litres, 4 Litres, 1 Litre