

PREMIUM



# Colourtrend SUPER GLOSS ENAMEL

<b>PRODUCT</b>	Colourtrend Super Gloss Enamel is a high quality synthetic enamel with an exceptionally hard and brilliant finish based on a synthetic alkyd resin and a carefully selected range of high quality pigments. It is resistant to abrasion, condensation and severe climatic conditions.
<b>FINISH</b>	Glossy
<b>COLOURS</b>	Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.
<b>AREA OF APPLICATION</b>	Colourtrend Super Gloss Enamel is recommended for both Interior and Exterior surfaces like metals, wooden surfaces, kitchens, walls, ceilings etc. under domestic & industrial applications. It is also used for doors, garden furniture & fittings and generally for exterior trims where a gloss finish, water resistance and accent on colour is required.

## TECHNICAL SPECIFICATION

<b>SPECIFIC GRAVITY</b>	1.05 ± 0.05
<b>COVERAGE</b>	Approximately 15 to 16 m <sup>2</sup> /litre per coat on smooth surface
<b>DRYING TIME</b>	Surface Dry : 3 - 5 Hours
	Hard dry : 6 - 8 Hours
	Recoating : After 24 Hours
<b>REMARK</b>	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

## METHOD OF APPLICATION

<b>SURFACE PREPARATION</b>	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Smoothen out with sand paper to provide required smoothness. Colourtrend Super Gloss Enamel should be applied over appropriately primed & undercoated surfaces
<b>EQUIPMENT</b>	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
<b>THINNING</b>	It can be thinned with white spirit depending on type of application.
<b>EQUIPMENT CLEANING</b>	Equipment should be cleaned immediately after use with white spirit.
<b>PACKING SIZE</b>	20 Litres, 4 Litres, 1 Litre