



Colourtrend VINYL MATT EMULSION

PRODUCT Colourtrend Vinyl Matt Emulsion is a high quality acrylic co-polymer based washable emulsion paint with a smooth, flat decorative finish. It is pigmented with specially selected pigments and fillers. Colourtrend Vinyl Matt Emulsion has a better hiding power and exceptional UV and weather resistance. It contains anti bacterial and anti fungal additives.

FINISH Matt

COLOURS Available in wide range of colours. Please refer to our shade card for standard available colours. Special colours can be manufactured on request.

AREA OF APPLICATION Colourtrend Vinyl Matt Emulsion is recommended for masonry application and protection of interior and exterior surfaces like concrete, plaster, gypsum board, asbestos etc. where a matt and durable finish is required. Major areas of application are buildings, apartments, offices, kitchens etc.

TECHNICAL SPECIFICATION	
SPECIFIC GRAVITY	1.50 ± 0.05
COVERAGE	Approximately 14 to 15 m ² /litre per coat depending on porosity of surface
DRYING TIME	Recoating after 3 - 4 Hours
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

METHOD OF APPLICATION	
SURFACE PREPARATION	Ensure that the surface to be painted is clean, dry and free from oil, grease or loose material. Fill up small cracks or dents with filler or putty. Smoothen out with sand paper to provide required smoothness. Colourtrend Super Vinyl Matt Emulsion should be applied over appropriately primed & undercoated surfaces
EQUIPMENT	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
THINNING	It can be thinned with fresh water depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with water.
PACKING SIZE	20 Litres, 4 Litres, 1 Litre