



# *Colourtrend* ZINC CHROMATE PRIMER YELLOW

**PRODUCT**                      Colourtrend Zinc Chromate Primer yellow is a premium quality anto corrosive primer for metal. It is based on a synthetic alkyd resin, speciality fillers and an anti corrosive pigments like Zinc Chromate.

**FINISH**                              Matt

**COLOURS**                          Yellow

**AREA OF APPLICATION**              Colourtrend Zinc Chromate Primer is recommended for protection of iron and steelwork exposed to humid air and salty atmosphere. It can be used on both interior and exterior, all Iron and steel surfaces and structures exposed to mild to highly corrosive atmosphere.

<u>TECHNICAL SPECIFICATION</u>	
<b>SPECIFIC GRAVITY</b>	1.05 ± 0.05
<b>COVERAGE</b>	Approximately 8 to 10 m <sup>2</sup> /litre per coat Depending on surface.
<b>DRYING TIME</b>	Surface Dry : 3 - 5 Hours
	Hard dry : 6 - 8 Hours
	Recoating : After 24 Hours
<b>REMARK</b>	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
<b>SURFACE PREPARATION</b>	Ensure that the surface to be primed is clean, dry and free from oil, grease or loose material. For most of iron and steel surfaces, Apply one coat of Colourtrend Zinc Chromate Primer, allow it to dry for 16 - 24 hours and then apply subsequent Undercoat or Topcoat.
<b>EQUIPMENT</b>	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
<b>THINNING</b>	It can be thinned with Maroo white spirit depending on type of application.
<b>EQUIPMENT CLEANING</b>	Equipment should be cleaned immediately after use with Maroo white spirit.
<b>PACKING SIZE</b>	20 Litres, 4 Litres, 1 Litre