



Colourtrend ZINC CHROMATE RED OXIDE PRIMER

PRODUCT Colourtrend Zinc Chromate Red Oxide Primer is a premium quality anti corrosive primer for metal. It is based on a synthetic alkyd resin and an anti corrosive pigments like Zinc Chromate & Red Oxide.

FINISH Matt

COLOURS Red

AREA OF APPLICATION Colourtrend Zinc Chromate Red Oxide Primer is recommended for protection of iron and steelwork exposed to humid air and salty atmosphere. It can be used on both interior and exterior, all Iron and steel surfaces and structures exposed to mild to highly corrosive atmosphere.

<u>TECHNICAL SPECIFICATION</u>	
SPECIFIC GRAVITY	1.05 ± 0.05
COVERAGE	Approximately 8 to 10 m ² /litre per coat Depending on surface.
DRYING TIME	Surface Dry : 3 - 5 Hours
	Hard dry : 6 - 8 Hours
	Recoating : After 24 Hours
REMARK	Atmospheric conditions like temperature and humidity, film thickness, interval of coats etc. can affect on drying time.

<u>METHOD OF APPLICATION</u>	
SURFACE PREPARATION	Ensure that the surface to be primed is clean, dry and free from oil, grease or loose material. For most of iron and steel surfaces, Apply one coat of Colourtrend Zinc Chromate red oxide Primer, allow it to dry for 16 - 24 hours and then apply subsequent Undercoat or Topcoat.
EQUIPMENT	Can be applied using brush, roller or by spraying. Thin and stir as per requirement
THINNING	It can be thinned with Maroo white spirit depending on type of application.
EQUIPMENT CLEANING	Equipment should be cleaned immediately after use with Maroo white spirit.
PACKING SIZE	20 Litres, 4 Litres, 1 Litre